

EURO TOWERS LTD

UK Manufacturer of Aluminium Access Equipment


KLIK SINGLE WIDTH LADDER FRAME 3T - THROUGH THE TRAPDOOR METHOD

TUV CERTIFIED QUALITY SYSTEM
TO ISO 9001:2015

GS PRODUCT APPROVAL TO
BS.EN.1004 3 8/12 XXXD

INSTRUCTIONS FOR USE TO BE
FOLLOWED CAREFULLY

TOWER MAX SAFE WORKING LOAD 750K | PLATFORM MAX SAFE WORKING LOAD 250KG



MANUFACTURED BY EURO TOWERS LTD

GENERAL SAFETY RULES

Before You Start

1. Familiarise yourself with these instructions paying attention to these safety notes before you use the equipment supplied. Towers may only be assembled and dismantled by a COMPETENT person familiar with these instructions.
2. User training courses cannot be a substitute for instruction manuals but only compliment them.
3. This product shall only be used according to the instruction manual.
4. Only original Euro Towers components specified in this manual shall be used.
5. It is recommended that this user manual be used in conjunction with a suitable risk assessment and method statement relative to the project.
6. This instruction manual shall be available to the USER at ALL times. Erection, alteration or dismantle of the tower should not be attempted unless the manual is present.
7. This mobile access and working tower shall only be used according to this manual without any modification.
8. Mobile access and working towers shall only be used in accordance with national regulations.
9. You will require the following PPE and Tools to help avoid personal injury, Hard Hat, Safety Gloves, Safety Shoes/Boots, Hi Vis vest/jacket and spirit level.
10. As part of your risk assessment do not begin to erect, move or dismantle your tower in excessive weather conditions including heavy rain, sleet or snow that can affect your anti slip surfaces. Also avoid working in extreme heat and high winds.
11. Ensure you selected the correct platform height tower in relation to the desired working height (usually 2m) to avoid over-reaching and other unsafe practices.
12. Inspect all individual components before use to ensure quantity, compatibility, any damages and all parts function correctly. Damaged or incorrect components shall NOT be used.
13. Check the quantity of components supplied corresponds correctly to the kitting list of the tower height you are planning to build. Do not start assembly if you do not have the correct number of components. Do not use any tower that has missing or damaged parts or has not been properly assembled.
14. Erect an exclusion zone and place warning signs if applicable to your location of work.
15. It is recommended that a minimum of two person erect, alter and dismantle a tower but during the risk assessment additional person(s) may be required to perform the task safely.

Inspection, Maintenance and transport

16. Regularly inspect the individual components to ensure that they are not damaged and function properly. Damaged components shall be isolated, tagged and removed from use. They should be replaced and sent for repair or scrap.
17. Inspect all tube on frames, stabilisers and braces for dents, cuts and holes, damaged equipment should be isolated, tagged and removed from use. Check all joints for cracked welds and that they are secure.
18. Inspect Brace Hooks, check the clicker is functioning correctly and the hook is not distorted from abuse. Check the brace is not bent/dented.
19. Inspect Platform for damage to the decking and fixings and that (if fitted) trapdoor open and close freely and the hinge is secure. Check the aluminium framework for damage and for cracked welds that may be damaged due to overloading. Check the hooks are not distorted from abuse and the wind lock clips are attached and functioning properly.
20. Inspect Stabiliser couplers tighten and can be loosened freely. Ensure rubber foot is securely fitted and not worn out. Check for adjusting pins on telescopic stabilisers are fitted and secured
21. Inspect castors, checking that the wheel turns and spins freely, that the brakes engage and stops the castor from spinning. Ensure the castor has no flat spots and has a SWL.
22. Inspect the adjustable leg threads are clear of burrs and the nut runs freely up and down the thread. Check the nut housing for abuse or missing nodules.
23. Light oil or lubricating spray may be used to free up jammed, clickers, castors, adjustable leg nuts, stabiliser couplers, trapdoor hinges and latches.
24. Do not put excessive loads on the components during storage.
25. When transporting the components do not use excessive strapping forces when securing the load, this may distort and damage components if not done with care.

Assembling and Dismantling

26. Check ground conditions are suitable for erecting and moving the tower and the ground can take the loads imposed by the tower including weight of equipment and persons. Do not assemble tower on unstable ground such as drain, manhole covers, compacted fill or any other hazards highlighted during the risk assessment.
27. Check for level and slope of the area where the tower is to be erected, moved and dismantled is within the levelling height of the adjustable legs.
28. Check for obstructions that could prevent erection, moving and dismantling of the tower safely.
29. Check for overhead hazards such as power lines. Do not assemble a tower near uninsulated, live or energised electrical machinery or circuits, or near machinery or plant that is in operation.
30. Ensure the Tower is level. Castor wheels should remain LOCKED unless moving the Tower. Adjustable legs are used for levelling the Tower. NEVER use to gain additional height. Extra height is gained by using additional compatible components. Other items such as ladders, steps, boxes etc should never be used to gain additional height.

GENERAL SAFETY RULES

31. All components should be passed up or down by hand where possible, where this is not possible use a suitable material for lifting (e.g. Heavy corded rope) and sufficient knot ties (e.g. hitch knot or timber hitch) DO NOT use mechanical hoists.
32. Towers MUST always be climbed from the inside for access and egress using the Integrated ladders or designated rungs. NEVER climb the outside of a Tower.
33. Do not lean ladders against a tower or climb the outside. Climb the ladder from the inside as per the supplied access system and use the trapdoor for access and egress.
34. Never climb on Diagonal or Horizontal braces. Never jump on to or off platforms
35. Working is only permitted on a platform with a complete side protection including guardrails and toe boards.
36. After assembly or alteration, the following minimum information shall be displayed on the tower:
 - a. The name and contact details of the person responsible
 - b. If the tower is ready for application or not
 - c. The load class and the uniformly distributed load
 - d. If the mobile access and working tower is intended for indoor use only
 - e. The date of assembly

Safe Use & Loadings

37. Before use, check that all components listed in the kit list have been used in the Tower in the correct position.
38. Care should be taken when using Power Tools or Jet washing or anything specific to your job that could imply side loads and cause the tower to overturn. Maximum permitted side load must not exceed 30kg (300N)
39. When lifting components or materials keep within the base of the Tower. Ensure the total weight of the User(s) any debris, materials being lifted does not exceed the Safe Working Load (SWL) of an individual platform (250kg) or the overall structure (750kg) Loads must be uniformly distributed on the working platform and not block trapdoors.
40. Mobile access and working towers designed in accordance with EN1004-1 are not anchor points for personal fall arrest equipment.
41. Work should only be completed from one Working Platform at any time complete with Guardrails and Toe Boards to prevent persons and materials falling from the tower. Work should not be attempted from any other part of the tower including stairs or braces.
42. The maximum number of person(s) permitted on the working platform at any time should not exceed the SWL (250kg). This should include any tools and or materials
43. You should never stand on an unprotected platform (guardrails must be in place)
44. Consider measures to secure the tower when left unattended.

Stability & Moving

45. Ensure the Tower is level and the adjustable legs are engaged. Check that you have taken all necessary precautions to prevent the Tower being moved or rolling away. Always apply ALL brakes or use base plates for static towers or inclined surfaces.
46. Ensure that the scaffold tower is within the maximum platform height as stated and that the appropriate stabilisers are fitted to suit. *Refer to kitting list.
47. A scaffold tower should not be used or moved in wind speeds stronger than 17mph (7.7meters per second) (Beaufort force 4). If wind speeds exceed this, consider tying the tower to a rigid structure or dismantling before it is exposed to the strong winds.
48. Beware of the potential wind factors where there is a possibility for the tunnelling effect of open-ended buildings, unclad building and at the corners of buildings
49. NEVER fit sheets or cladding to a Tower. Such items can act as a sail and impose extreme horizontal load onto a tower causing it to overturn.
50. When moving a tower plan the route, removing any obstructions, ensuring the ground can take the weight of the tower. Beware of soft and uneven ground. Pay attention for overhead hazards and ensure that all materials and persons are removed from the Tower. If there are any doubts about the route, then dismantle and erect in new location.
51. Towers should only be moved manually by pushing at the base of the tower at a usual walking speed. The Tower height should be reduced to 4m if all 4 stabilisers are in place and 2m if less than 4 stabilisers are in place. Stabilisers are raised approximately 25mm clear of the ground and then castors are unlocked and the tower can be moved.
52. When the Tower is repositioned reapply the brakes on castor wheels and the tower shall be levelled using the adjustable legs for both horizontal and vertical alignment. The stabilisers can then be lowered making firm contact with the ground.
53. Towers should NEVER be lifted or suspended by a crane or moved by mechanical means
54. Towers are not designed to be used as a means to enter or exit other structures
55. Towers are not designed to be used as a means of edge protection
56. All towers should be inspected before use.

Further information on inspection and maintenance can be found on Euro Towers inspection posters. For further safety information or downloading instructions call Euro Towers or visit our website. www.eurotowers.co.uk

3T LADDER FRAME SCAFFOLD TOWER SINGLE WIDTH KIT LIST

Available in three lengths: 2m, 2.5m or 3m

WORK HEIGHT	3.41m	3.88m	4.34m	4.81m	5.27m	5.73m
OVERALL TOWER HEIGHT	2.66m	3.13m	3.59m	4.06m	4.53m	4.98m
PLATFORM HEIGHT	1.41m	1.88m	2.34m	2.81m	3.27m	3.73m
PARTS LIST						
CASTOR	4	4	4	4	4	4
ADJUSTABLE LEG	4	4	4	4	4	4
3 RUNG FRAME		2	1			2
3 RUNG LADDER FRAME		2	1			2
4 RUNG FRAME			1	2	1	1
4 RUNG LADDER FRAME			1	2	1	1
5 RUNG FRAME	1				1	
5 RUNG LADDER FRAME	1				1	
DIAGONAL BRACE	2	2	3	3	4	4
HORIZONTAL BRACE	6	6	6	10	10	10
TRAPDOOR PLATFORM	1	1	2	2	2	2
STANDARD STABILIZER		4	4	4	4	4
TELESCOPIC STABILIZER						
TOEBOARD ASSEMBLY	1	1	1	1	1	1
TOWER WEIGHT (Kgs)						
2m WEIGHT	80	94	114	125	130	136
2.5m WEIGHT	82	104	127	139	145	151
3m WEIGHT	88	110	138	152	158	164
COMPONENT WEIGHT (Kgs)						
2 Rung Single Width Plain Frame	FKS2	4.02	Single Width Guardrail		FKSG	3.09
3 Rung Single Width Plain Frame	FKS3	5.46	2M Plain Platform		PKP1	13.22
4 Rung Single Width Plain Frame	FKS4	6.81	2.5M Plain Platform		PKP2	16.88
5 Rung Single Width Plain Frame	FKS5	8.05	3M Plain Platform		PKP3	20.29
2 Rung Single Width Ladder Frame	FSL2	5.22	2M Trapdoor Platform		PKT1	13.48
3 Rung Single Width Ladder Frame	FSL3	7.23	2.5M Trapdoor Platform		PKT2	17.38
4 Rung Single Width Ladder Frame	FSL4	9.36	3M Trapdoor platform		PKT3	21.83
5 Rung Single Width Ladder Frame	FSL5	11.38				

MOVING A TOWER Remove people and materials from the tower, and lower the tower to 4m if all 4 stabilisers are in place. If not then reduce tower height to 2m. Adjust and raise the stabilizers 25mm from the ground, ensure the couplers are tight, and push from at or near the base by manual effort only, never use mechanical means. Recheck level and reposition stabilizers before use.

ALTERNATIVE FRAMES CONFIGURATION: For example where 2 x 4 rung frames are stated making the tower 8 rungs in total, these can be replaced by 1 x 5 rung and 1 x 3 rung, also making 8 rungs in total.


6.20m	6.66m	7.13m	7.59m	8.05m	8.52m	8.98m	9.45m	9.91m
5.45m	5.91m	6.38m	6.84m	7.30m	7.77m	8.23m	8.70m	9.16m
4.20m	4.66m	5.13m	5.59m	6.05m	6.52m	6.98m	7.45m	7.91m
4	4	4	4	4	4	4	4	4
4	4	4	4	4	4	4	4	4
1			2	1			2	1
1			2	1			2	1
2	3	2	2	3	4	3	3	4
2	3	2	2	3	4	3	3	4
		1				1		
		1				1		
5	5	6	6	7	7	8	8	9
10	10	14	14	14	14	18	18	18
2	2	3	3	3	3	4	4	4
4	4							
		4	4	4	4	4	4	4
1	1	1	1	1	1	1	1	1
142	145	157	163	190	193	198	204	210
157	160	172	178	210	214	219	225	231
170	174	186	192	229	234	240	245	252
2M Horizontal Brace		BKH1	1.93	5" Castor		K5CR	3.23	
2.5M Horizontal Brace		BKH2	2.24	6" Castor		K6CR	3.65	
3M Horizontal Brace		BKH3	2.55	8" Castor		K8CR	4.34	
2M Diagonal Brace		BKD1	2.06	Adjustable Leg		KALA	0.98	
2.5M Diagonal Brace		BKD2	2.35	Standard Stabilizer		SKS1	4.02	
3M Diagonal Brace		BKD3	2.65	Large Stabilizer		SKL2	7.84	
Swivel Base Plate		KSBP	1.03	Telescopic Stabilizer		Y250	5.66	

PPE REQUIRED: Hard Hat, Safety Gloves, Safety Boots/Shoes, Hi-Viz Vest/Jacket
TOOLS REQUIRED: Spirit Level


STABILIZERS

Stabilizers increase the EFFECTIVE BASE dimensions and improve the STABILITY of the tower. Position the stabilizers symmetrically to obtain the MAXIMUM BASE DIMENSION.

PLATFORM HEIGHTS	MAXIMUM HEIGHT	STABILIZER TYPE
0m	1.41	NONE
1.88m	4.66m	STANDARD
5.13m	7.91m	TELESCOPIC



Free Standing Tower




Against a Wall



In a Corner

SINGLE WIDTH LADDER FRAME ERECTION INSTRUCTION MANUAL

**The tower requires a minimum of 2 people for assembly
Do not attempt to assemble a tower by yourself**



Bracing Positions

On rungs with two braces and a platform you will need to have one brace sitting on the inside of the platform hook and one sitting on the outside of the platform hook. You will also need to offset the platform to one side to achieve this. Alternatively diagonal braces can be repositioned 1 rung above or 1 rung below the platform.



Figure 1

3/3 Rung Base Set Up

For Platform Heights:

1.88m, 3.73m, 5.59m, 7.45m,

When using this frame configuration. Start your diagonal brace pattern from 2nd to 4th in an alternate pattern. Offset trapdoor platform to one side allowing a diagonal brace to continue in a regular pattern.

3/4 Rung Base Set Up

For Platform Heights:

2.34m, 4.20m, 6.05m, 7.91m

To achieve platform heights 2.34m, 4.2m, 6.05, or 7.91m you will need to fit a temporary platform on the 1st rung. (See Figure 2)

Fit access platform from 3rd rung down on the 4 rung frame from the temporary platform. Fit handrails from 3T position. Remove temporary platform and guardrails then reposition 2 diagonal braces from 1st to 3rd rungs in a alternate patter and install 1 additional diagonal brace from the 3rd to 5th rung. (See figure 3)



Figure 2



Figure 3



Figure 4

5 Rung Base Set Up

For Platform Heights:

1.41m, 3.27m, 5.13m 6.98m

Fit platform on third rung down. This base build does not require repositioning of the platform.



Figure 5



Figure 6

4/4 Rung Base Set Up

For Platform Heights:

2.81m, 4.66m, 6.52m

To achieve platform heights 2.81m, 4.66m and 6.52m you will need to fit a temporary platform to the 3rd rung down. (See figure 5).

Then Fit 4 horizontal braces from the ground around the temporary platform. From the temporary platform add both 4 rung frames and fit your platform on the 3rd rung down from the top. Remove your temporary board and guardrail braces. Then reposition your diagonal brace to 1st to 3rd and add an additional brace on the alternative side. Finally add an additional diagonal brace from 3rd to 5th. (See Figure 6)

BASE SET UPS:


WORKING PLATFORM	BASE FRAME	NEXT FRAME	FURTHER FRAMES**	PLATFORM RUNG POSITIONS
1.41m / 3.27m / 5.13m / 6.98m	5 RUNG	4 RUNG	4 RUNG	3* 7 11 15
1.88m / 3.73m / 5.59m / 7.45m	3 RUNG	3 RUNG	4 RUNG	4* 8 12 16
2.34m / 4.20m / 6.05m / 7.91m	3 RUNG	4 RUNG	4 RUNG	1* 5 9* 13 17
2.81m / 4.66m / 6.52m	4 RUNG	4 RUNG	4 RUNG	2* 6 10 14
*REPOSITION PLATFORMS WHERE REQUIRED			**SEE USING ALTERNATIVE FRAMES NOTE	



1. Insert castor wheels into adjustable legs



2. Insert 2 adjustable legs and castor wheels into each base frame



3. Lock Brakes and allow 3" thread from bottom of castor for levelling



4. Fit 2 horizontal braces to the vertical member of the frames above first rung. Horizontal braces fit on from the inside of the tower facing outwards



5. Fit 1 plain platform on the appropriate rung. (See base build for desired platform height). Level your tower by the adjustable legs using a spirit level as a guide.

The scaffold must be vertical in both planes within an inclination of 1%

NEVER STAND ON AN UNPROTECTED PLATFORM



6. Add further frames ensuring the ladder is continuous.



7. After adding frames always remember to engage interlock clips



8. Fit 2 more diagonal braces to continue in a regular pattern on the rung above the first platform.



9. Fit 4 horizontal braces directly above platform to create your collective protection. Hooks facing outwards on frame uprights.



10. Fit 4 stabilisers at earliest opportunity keeping lower arm as horizontal as possible.



11. From the temporary platform, fit 1 diagonal brace to 3rd rung down and fit trapdoor platform over the hook. Offset platform to oneside.



12. Remove temporary platform and the 4 horizontal braces. Relocate 2 diagonal braces from 2nd to 1st rung.



13. From a seated position using the through the trapdoor (3T) method. Fit 4 horizontal braces, hooks facing outwards to the frame upright.



14. Continue erecting the tower fitting the frames and diagonal braces as illustrated using all components. Platforms inserted every 2m complete with handrails. Braces run in a continuous pattern on opposite sides.




15. For your working platform fit trapdoor on the 3rd rung down from the top of the tower.



16. From a seated position, using the 3T method, fit 4 horizontal braces above the appropriate rungs to the frame vertices, hooks facing out.



17. Fit toe-boards in correct position



DISMANTLE TOWER IN REVERSE EXCEPT WHEN DISMANTLING THE HANDRAILS




Unclip 4 x Horizontal braces from the far end of the trapdoor platform.




From a seated position remove 4 x guardrails making sure you never stand on an unprotected platform.



From a seated position descend down the tower to the next platform or ground. Ensure you always have collective protection around you when standing on any platform.




Maximum distance between platforms shall not exceed 2.25m except the distance to the first platform max 3.40m



Do not bridge between towers or other structures Please contact Euro Towers for information on the correct equipment for Bridging Towers




Maximum inclination for **movement**. Note the maximum angle allowed is defined by the manufacturer




Do not build, dismantle or attempt to work on an access tower if the wind speed exceeds 17MPH




Maximum inclination for movement. Note the maximum angle allowed is defined by the manufacturer




Do not stand on an unguarded platform




Do not lift the tower with mechanical equipment



Do not use the tower for access and egress to other structures



Do not suspend the tower




Do not lift heavy objects from the tower



Do not move the tower with people or materials on it



Do not use ladders, boxes or other objects to gain extra height



Do not climb the outside of the tower

